

Fume Extractors

Model references: FAE1, FAE2

Error num.	Displayed message	Solution
1	WARNING #1 Useful filter life is about to wear out. In X days the filter life is going to finish. STOP #1 Useful filter life is worn out. Replace it and execute	Replace the filter and reset it.
2	reset function in the filter menu. WARNING #2 Filter is about to obstruct. STOP #2 Filter obstructed. Replace the pre-filter, if the error remains, replace the HEPA+carbon filter set.	Replace the prefiltrer. If the warning persists, replace the HEPA+Coal. If the problem is not solved, contact the Technical Service.
3	STOP #3 Filter not detected. Place a filter in order to use the fume extractor.	Put a filter, if the error persists, contact with the technical support.
4	STOP #4 Cover opened or badly closed. Double check the cover.	Take the cover off and put it again. Clean the contacts of the cover and the base (only for FAE2). Fit the close mechanism. If the problem is not solved, contact the Technical Service.
5	STOP #5 Blower damaged. Contact with technical service.	Contact with the technical support.
7	STOP #7 Valve X error. Restart the unit, if the error remains, replace the valve.	Take the cover off and clean the contacts of the cover and the base. Next, restart the station. Take off the cover, Fit the close mechanism and reset the station. Replace the valve and restart the station. If the problem is not solved, contact the Technical Service.
8	STOP #8 Overcurrent detected in auxiliary port. Disconnect the peripheral and check it before connecting again.	Take the connected peripheral off in the Aux port. If in 10 seconds, the error persists, contact with the Technical Service.
9	STOP #9 Pedal error in port X. Replace the pedal.	Disconnect the pedal from the specified port. If the problem is not solved, contact the Technical Service.
10	STOP #10 System error. Restart the unit, if the error remains, contact with technical service.	Restart the station. If not solved, contact with the Technical Service.
11	STOP #11 System error. Restart the unit, if the error remains, contact with technical service.	